

## ALUMINIUM 2014 - AMS 4029

|   |                                  |                             |                               |                              |                 |
|---|----------------------------------|-----------------------------|-------------------------------|------------------------------|-----------------|
| <b>Specific Gravity</b>   |                                  |                             |                               |                              |                 |
|   |                                  |                             |                               |                              |                 |
| <b>Typical Applications</b>   |                                  |                             | <b>Related Specifications</b> |                              |                 |
|   |                                  |                             | L93                           |                              |                 |
| <b>Chemical Composition (Wt %)</b>  |                                  |                             |                               |                              |                 |
|   |                                  |                             |                               |                              |                 |
| <b>Min</b>  |                                  |                             |                               |                              |                 |
| <b>Max</b>  |                                  |                             |                               |                              |                 |
| <b>Typical Mechanical Properties</b>  |                                  |                             |                               |                              |                 |
|   | <b>0.2%<br/>Proof<br/>Stress</b> | <b>Tensile<br/>Strength</b> | <b>Elongation</b>             | <b>Reduction<br/>of area</b> | <b>Hardness</b> |
|   |                                  |                             |                               |                              |                 |
| <b>Content</b>  |                                  |                             |                               |                              |                 |
|   |                                  |                             |                               |                              |                 |
| <b>Hardness after Heat Treatment</b>  |                                  |                             |                               |                              |                 |
|   |                                  |                             |                               |                              |                 |
| <p>* Every effort has been made to ensure that our technical specifications are accurate. However, technical specifications included within Dynamic Metals Ltd should be used as a guideline only and are subject to change without notice.</p> |                                  |                             |                               |                              |                 |

### General Enquiries

T: +44 (0) 1525 217 556 [\\_\(tel:+4401525217556\)](tel:+4401525217556)

E: [sales@dynamicmetalsltd.com](mailto:sales@dynamicmetalsltd.com) [\\_\(mailto:sales@dynamicmetalsltd.com\)](mailto:sales@dynamicmetalsltd.com)



## **UK Address:**

### *Head Office*

40 Eden Way  
Chartwell Business Park  
Leighton Buzzard  
Bedfordshire  
LU7 4FY

T: +44 (0)1525 217 556 [\\_\(tel:+441525217556\)](tel:+441525217556)

### *Conversion Centre*

Suite 2 Meadowhall Riverside  
Meadowhall Road  
Sheffield  
South Yorkshire  
S9 1BW

T: +44 (0)1143 030 320 [\\_\(tel:+4401143030320\)](tel:+4401143030320)

### *Registered Office (only)*

The Granary  
Crowhill Farm Ravensden Road  
Wilden  
Bedfordshire  
MK44 2QS

T: +44 (0)1525 217 556 [\\_\(tel:+441525217556\)](tel:+441525217556)



[\(/media/zn2dbklo/cyber-essentials-certified-plus.png\)](#)



[\(/media/dyelbliq/cyber-essentials-certified.png\)](#)