AMS 4911 - TÔLES TITANE TA6V

Applications typiques

Disques de compresseur et pales de ventilateur

Composants de cellule d'aéronef

Composants de transmission pour le sport automobile

Applications sous-marines en environnement corrosif (sour service)

Le TA6V (AMS 4911) est un alliage de Titane pouvant être traité pour une amélioration modérée de sa résistance. Il offre une combinaison de légèreté, de haute résistance mécanique, de formabilité et de résistance à la corrosion le rendant très attractif pour de nombreuse application dans le milieu de l'aéronautique, du sport mécanique et du médical.

Spécification technique

Spécifications connexes

AMS 4911

Mil T 9046

ASTM B265

TA10

TA56

TA59

UNS R56400

MSRR 8633

Densité spécifique

4.484 g/cm3

Composition chimique (WT %)

C - 0.0		Min	Max
C - 0.0			
	С	-	0.08

03/12/2025 05:39 1 of 3

Al	5.5	6.75
N	-	0.05
0	-	0.2
Ti	-	Bal
V	3.50	4.50
Fe	-	0.25
Н	-	0.01
Υ	-	0.005

Typical Mechanical Properties in the Annealed condition

0.2% Proof Stress	MPA	Min	830
Tensile Strength	MPA	Min	900
Elongation	%	Min	8
Reduction of Area	%	Min	20

03/12/2025 05:39 2 of 3

Need more information? Get in touch

General Enquiries

+44(0) 1525 217 556

Email us here

Head Office

40 Eden Way Chartwell Business Park Leighton Buzzard Bedfordshire LU7 4FY

T: +44 (0)1525 217 556

Conversion Centre

Suite 2 Meadowhall Riverside Meadowhall Road Sheffield South Yorkshire S9 1BW

T: +44 (0)1143 030 320

Useful Links

Privacy Policy

Sitemap





03/12/2025 05:39 3 of 3