

15CDV6 TUBE

15CDV6 is a low carbon alloy steel with very good yield strength. It also has very good toughness and excellent weldability. Welding can be achieved without subsequent heat treatment and with negligible loss of properties.

Related Specs - W.Nr 1.7734, AIR 9160C, GT1000

Specific Gravity								
7.8 g/cm3								
Typical Applications					Related Specifications			
Roll Cages Pressure Vessels Rocket Motor Casings Subframes Track and Push rods Wishbones Uprights					W.Nr 1.7734 AIR 9160C GT1000			
Chemical Composition (Wt %)								
	C	Si	Mn	S	P	Cr	Mo	V
Min	0.12	–	0.80	–	–	1.25	0.80	0.20
Max	0.18	0.20	1.10	0.015	0.020	1.50	1.00	0.30
Mechanical Properties								
	0.2% Proof Stress	Tensile Strength	Elongation	Hardness				
Condition	MPA (min)	MPA (min)	%	HB				
1.7734.2 (Annealed)	–	–	–	197				
1.7734.4	550	700	13	207				

1.7734.5	790	980-1180	11	293-352
1.7745.6	930	1080-1250	10	231-363

* This data has been supplied in good faith and is indicative only. It has been provided for general information purposes only and is not to be relied upon in place of the full specification. Mechanical properties can vary considerably with different supply conditions such as heat treatment or temper and product dimensions.

No liability will be accepted by Dynamic Metals Ltd in respect of any action taken by any third party in reliance of any of the data provided.

The information provided in this datasheet has been taken from multiple recognised sources. No guarantee is given that the information is from the latest issue of these sources and no guarantee is given that the information in the datasheet is accurate or up to date.

Material supplied by Dynamic Metals Ltd may vary significantly from this data but will conform to the relevant and applicable standards. All transactions are subject to Dynamic Metals Ltd latest Terms and Conditions of Sale.

As the products detailed may be used for a wide variety of purposes and as Dynamic Metals Ltd has no control over their use; Dynamic Metals Ltd specifically excludes all conditions or warranties expressed or implied by statute or otherwise as to dimensions, properties and/or fitness for any particular purpose, whether expressed or implied.

Advice given by Dynamic Metals Ltd to any third party is given for that party's assistance only and without liability on the part of Dynamic Metals Ltd.

All transactions are subject to Dynamic Metals Ltd latest Terms and Conditions of Sale. The extent of the Company's liabilities to any customer is clearly set out in those Conditions; a copy of which is available by request or by downloading from our website.

General Enquiries

T: +44 (0) 1525 217 556 [\(tel:+4401525217556\)](tel:+4401525217556)

E: sales@dynamicmetalsltd.com [\(mailto:sales@dynamicmetalsltd.com\)](mailto:sales@dynamicmetalsltd.com)



UK Address:

Head Office

40 Eden Way
 Chartwell Business Park
 Leighton Buzzard
 Bedfordshire
 LU7 4FY

T: +44 (0)1525 217 556 [\(tel:+441525217556\)](tel:+441525217556)

Conversion Centre

Suite 2 Meadowhall Riverside
 Meadowhall Road
 Sheffield
 South Yorkshire
 S9 1BW

T: +44 (0)1143 030 320 [\(tel:+4401143030320\)](tel:+4401143030320)

Registered Office (only)

The Granary
Crowhill Farm Ravensden Road
Wilden
Bedfordshire
MK44 2QS

T: +44 (0)1525 217 556 [_tel:+441525217556](tel:+441525217556)



[\(/media/zn2dbklo/cyber-essentials-certified-plus.png\)](#)



[\(/media/dyelbliq/cyber-essentials-certified.png\)](#)