

AMS 6350, AMS 6345 - 4130 ALLOY STEEL SHEETS AND PLATES

4130 is a through hardening low alloy steel containing molybdenum and chromium as strengthening agents. 4130 responds well to nitriding for very good wear and abrasion resistance.

Specific Gravity							
7.8 g/cm ³							
Typical Applications				Related Specifications			
Aircraft seating Roll Cages Motorsport applications				AMS 6350 AMS 6345 UNS G41300			
Chemical Composition (Wt %)							
	C	Mn	P	S	Si	Cr	Mo
Min	0.28	0.40	–	–	0.15	0.80	0.15
Max	0.33	0.60	0.025	0.025	0.35	1.10	0.25
Typical Mechanical Properties							
	0.2% Proof Stress	Tensile Strength	Elongation				
	MPA	MPA	%				
Annealed		586					
Normalised							
Up to 0.062"	517	655	8				
0.062" – 0.125"	517	655	10				
0.125" – 0.187"	517	655	12				
0.187" – 0.249"	482	620	15				

0.249" – 0.749"	482	620	16
0.749" – 1.5"	482	620	18

* This data has been supplied in good faith and is indicative only. It has been provided for general information purposes only and is not to be relied upon in place of the full specification. Mechanical properties can vary considerably with different supply conditions such as heat treatment or temper and product dimensions.

No liability will be accepted by Dynamic Metals Ltd in respect of any action taken by any third party in reliance of any of the data provided.

The information provided in this datasheet has been taken from multiple recognised sources. No guarantee is given that the information is from the latest issue of these sources and no guarantee is given that the information in the datasheet is accurate or up to date.

Material supplied by Dynamic Metals Ltd may vary significantly from this data but will conform to the relevant and applicable standards. All transactions are subject to Dynamic Metals Ltd latest Terms and Conditions of Sale.

As the products detailed may be used for a wide variety of purposes and as Dynamic Metals Ltd has no control over their use, Dynamic Metals Ltd specifically excludes all conditions or warranties expressed or implied by statute or otherwise as to dimensions, properties and/or fitness for any particular purpose, whether expressed or implied.

Advice given by Dynamic Metals Ltd to any third party is given for that party's assistance only and without liability on the part of Dynamic Metals Ltd.

All transactions are subject to Dynamic Metals Ltd latest Terms and Conditions of Sale. The extent of the Company's liabilities to any customer is clearly set out in those Conditions; a copy of which is available by request or by downloading from our website.

General Enquiries

T: +44 (0) 1525 217 556 [\(tel:+4401525217556\)](tel:+4401525217556)

E: sales@dynamicmetalsltd.com [\(mailto:sales@dynamicmetalsltd.com\)](mailto:sales@dynamicmetalsltd.com)



UK Address:

Head Office

40 Eden Way
 Chartwell Business Park
 Leighton Buzzard
 Bedfordshire
 LU7 4FY

T: +44 (0)1525 217 556 [\(tel:+441525217556\)](tel:+441525217556)

Conversion Centre

Suite 2 Meadowhall Riverside
 Meadowhall Road
 Sheffield
 South Yorkshire
 S9 1BW

T: +44 (0)1143 030 320 [\(tel:+4401143030320\)](tel:+4401143030320)

Registered Office (only)

The Granary
 Crowhill Farm Ravensden Road
 Wilden

Bedfordshire
MK44 2QS

T: +44 (0)1525 217 556 [_\(tel:+441525217556\)](tel:+441525217556)



[\(/media/zn2dbklo/cyber-essentials-certified-plus.png\)](/media/zn2dbklo/cyber-essentials-certified-plus.png)



[\(/media/dyelbliq/cyber-essentials-certified.png\)](/media/dyelbliq/cyber-essentials-certified.png)