

AMS 6350, AMS 6345 - 4130 Alloy Steel Sheets And Plates

Typical Applications

Aircraft seating

Roll Cages

Motorsport applications



4130 is a through hardening low alloy steel containing molybdenum and chromium as strengthening agents. 4130 responds well to nitriding for very good wear and abrasion resistance.

Related Products

15Cdv6 Bar Sheet Tube

300M

4130 Bar And Tube

4130 Sheet And Plate

4340

52100

S99

EN24

Hy Tuf

S156

T45

M50 Steel Bar

4330 Alloy Steel

BS S106

Technical specification

Related Specifications

AMS 6350

AMS 6345

UNS G41300

Specific Gravity

7.8 g/cm³

Chemical Composition (WT %)

	Min	Max
C	0.28	0.33
Mn	0.40	0.60
P	-	0.025
S	-	0.025
Si	0.15	0.35
Cr	0.80	1.10
Mo	0.15	0.25

Typical Mechanical Properties

		Annealed	Normalised	Up to 0.062"	0.062" – 0.125"	0.125" – 0.187"	0.187" – 0.249"	0.249" – 0.749"	0.749" – 1.5"
0.2% Proof Stress	MPA	-	-	517	517	517	482	482	482
Tensile Strength	MPA	586	-	655	655	655	620	620	620
Elongation	%	-	-	8	10	12	15	16	18

The data are based on typical properties and a representative specimen geometry for general information only. It is not intended to be used for design purposes. Mechanical properties may vary significantly with different grades, conditions and heat treatments. Contact your supplier for more information.

The results of all mechanical tests are based on a representative specimen geometry and are not intended to be used for design purposes.

The information provided in this document is based on multiple measurements. The standard deviation of the mean is shown in the table. The standard deviation of the mean is shown in the table. The standard deviation of the mean is shown in the table.

These properties are based on a representative specimen geometry and are not intended to be used for design purposes.

The data are based on typical properties and a representative specimen geometry for general information only. It is not intended to be used for design purposes. Mechanical properties may vary significantly with different grades, conditions and heat treatments. Contact your supplier for more information.

The results of all mechanical tests are based on a representative specimen geometry and are not intended to be used for design purposes.

The information provided in this document is based on multiple measurements. The standard deviation of the mean is shown in the table. The standard deviation of the mean is shown in the table. The standard deviation of the mean is shown in the table.

These properties are based on a representative specimen geometry and are not intended to be used for design purposes.

Need more information? **Get in touch**

General Enquiries

+44(0) 1525 217 556

Email us here

Head Office

40 Eden Way
Chartwell Business Park
Leighton Buzzard
Bedfordshire
LU7 4FY

T: +44 (0)1525 217 556

Conversion Centre

Suite 2 Meadowhall Riverside
Meadowhall Road
Sheffield
South Yorkshire
S9 1BW

T: +44 (0)1143 030 320

Useful Links

[Privacy Policy](#)

[Sitemap](#)

