

52100 ALLOY STEEL - AMS 6444

52100 alloy steel is a type of bearing steel prized for its exceptional hardness and wear resistance. 52100 is a carefully crafted high carbon, chromium alloy steel that has been engineered to deliver exceptional durability and robust strength.

When properly heat treated, 52100 steel can achieve incredibly high hardness values, up to 66 Rockwell C. This hardness allows components made from 52100 to better withstand intense mechanical stresses, abrasive wear, and surface fatigue over extended periods of use. It has excellent corrosion resistance due to the high chromium content.

While its hardness makes 52100 incredibly tough and long lasting, it also means the steel is quite brittle compared to other steel grades. While incredibly hard and resilient, the alloy does sacrifice some malleability and resistance to impact forces. Care must be taken during machining and fabrication to avoid introducing microscopic cracks and defects that could lead to catastrophic failures down the line.

For this reason, 52100 is an alloy utilised primarily for parts and components that experience punishing conditions but require little deformation during operation. You'll find it used in a variety of harsh industrial settings like bearings, bushings, cams, shafts, and other high-load, high-wear applications where tremendous hardness and resilience is paramount.

When sourced from a trusted supplier and properly processed through controlled heat treatment, 52100 delivers unparalleled longevity making it the premier steel for ultra-demanding use cases.

Specific Gravity											
7.81 g/cm3											
Typical Applications						Related Specifications					
Bearings Fasteners						AMS 6440					
						AMS 6444					
						SA5589					
						AIR 9160C					
Chemical Composition (Wt %)											
	C	Mn	Si	P	S	Cr	Ni	Mo	Cu	Al	O
Min	0.93	0.25	0.15	-	-	1.35	-	-	-	-	-
Max	1.05	0.45	0.35	0.015	0.015	1.60	0.25	0.1	0.3	0.05	0.015
Typical Mechanical Properties											

	0.2% Yield Strength	Tensile Strength	Elongation	Reduction of area	Hardness
	MPA	MPA	%	%	HBW
Round Bar	427	651	27	62.5	179

What is 52100 Steel?

52100 is an incredibly robust alloy steel that makers turn to when only the highest levels of hardness and durability will do. It's a finely tuned chromium and carbon blend that, through meticulous heat treatment, can achieve astonishing hardness ratings up to 66 Rockwell C. This unique metallurgical makeup allows components forged from 52100 to simply shrug off the kind of punishing conditions that would quickly deteriorate lesser steels.

While its incredible hardness does limit some flexibility, 52100 excels in harsh, unforgiving industrial environments where maximum wear and fatigue resistance take precedence. You'll find this premium alloy steel hard at work in bearings, bushings, shafts, and any other application where longevity and resilience under high stress is an absolute must. When your demands are extreme, 52100 delivers in a way that few other materials can match.

What material is AMS 6440?

AMS 6440 is the aerospace material specification for a premium grade of stainless steel. What sets AMS 6440 apart is its impressive ability to combine corrosion resistance with immense strength and durability - a combination perfectly suited for components that absolutely cannot fail, even under the most extreme conditions.

Developed specifically for aircraft and spacecraft applications, AMS 6440 can easily withstand intense mechanical stresses, temperature extremes, and harsh operating conditions. The stellar durability of AMS 6440 means components can be lighter and thinner than what other steel alloys allow, without sacrificing strength.

You'll find this ultra-tough stainless steel in some of the most critical areas of aircraft and spacecraft - whether turbine engines and landing gear or structural members and fasteners. Across both commercial and military aviation, when uncompromising performance is demanded, AMS 6440 delivers. When safety and reliability are non-negotiable, manufacturers turn to the proven performance of AMS 6440.

What are the typical uses for 52100 Alloy Steel?

52100 alloy steel excels for severe-duty bearings, bushings, and wear components subjected to intense temperatures, loading, and hostile environments. Its exceptional hardness and wear resistance make it ideal for aircraft engines, machine tooling, offshore equipment, and any application demanding ultra-hard, durable components.

* This data has been supplied in good faith and is indicative only. It has been provided for general information purposes only and is not to be relied upon in place of the full specification. Mechanical properties can vary considerably with different supply conditions such as heat treatment or temper and product dimensions.

No liability will be accepted by Dynamic Metals Ltd in respect of any action taken by any third party in reliance of any of the data provided.

The information provided in this datasheet has been taken from multiple recognised sources. No guarantee is given that the information is from the latest issue of these sources and no guarantee is given that the information in the datasheet is accurate or up to date.

Material supplied by Dynamic Metals Ltd may vary significantly from this data but will conform to the relevant and applicable standards. All transactions are subject to Dynamic Metals Ltd latest Terms and Conditions of Sale.

As the products detailed may be used for a wide variety of purposes and as Dynamic Metals Ltd has no control over their use, Dynamic Metals Ltd specifically excludes all conditions or warranties expressed or implied by statute or otherwise as to dimensions, properties and/or fitness for any particular purpose, whether expressed or implied.

Advice given by Dynamic Metals Ltd to any third party is given for that party's assistance only and without liability on the part of Dynamic Metals Ltd.

All transactions are subject to Dynamic Metals Ltd latest Terms and Conditions of Sale. The extent of the Company's liabilities to any customer is clearly set out in those Conditions; a copy of which is available by request or by downloading from our website.

General Enquiries

T: +44 (0) 1525 217 556 [_\(tel:+4401525217556\)](tel:+4401525217556)

E: sales@dynamicmetalsltd.com [_\(mailto:sales@dynamicmetalsltd.com\)](mailto:sales@dynamicmetalsltd.com)



UK Address:

Head Office

40 Eden Way
Chartwell Business Park
Leighton Buzzard
Bedfordshire
LU7 4FY

T: +44 (0)1525 217 556 [_\(tel:+441525217556\)](tel:+441525217556)

Conversion Centre

Suite 2 Meadowhall Riverside
Meadowhall Road
Sheffield
South Yorkshire
S9 1BW

T: +44 (0)1143 030 320 [_\(tel:+4401143030320\)](tel:+4401143030320)

Registered Office (only)

The Granary
Crowhill Farm Ravensden Road
Wilden
Bedfordshire
MK44 2QS

T: +44 (0)1525 217 556 [_\(tel:+441525217556\)](tel:+441525217556)



[\(/media/zn2dbklo/cyber-essentials-certified-plus.png\)](#)



[\(/media/dyelbliq/cyber-essentials-certified.png\)](#)