

Titanium Grade 2 Bar - ASTM B348

Typical Applications

- Acetabular cups
- Brackets
- Condensors
- Cryogenic vessels
- Jigs
- Cathodes

Titanium Grade 2 is a commercially pure form of titanium. It is widely used because it combines excellent formability and moderate strength with superior corrosion resistance.

This combination of properties makes Grade 2 titanium ideal for a large variety of chemical and marine as well as aerospace and medical applications.

Technical specification

Related Specifications

ASTM B348

ASTM F67

AMS T 9047

NACE MR01-75

UNS R50400

W.Nr 3.7034

Chemical Composition (WT %)

	Min	Max
C	-	0.08
N	-	0.03

O	-	0.250
Ti	-	Bal
Fe	-	0.30
H	-	0.015
Other	-	0.40

Typical Mechanical Properties in the Annealed condition

0.2% Proof Stress	MPA	Min	275
Tensile Strength	MPA	Min	345
Elongation	%	Min	20
Reduction of Area	%		30
Hardness	HRB		80

Need more information? **Get in touch**

General Enquiries

+44(0) 1525 217 556

Email us here

Head Office

40 Eden Way
Chartwell Business Park
Leighton Buzzard
Bedfordshire
LU7 4FY

T: +44 (0)1525 217 556

Conversion Centre

Suite 2 Meadowhall Riverside
Meadowhall Road
Sheffield
South Yorkshire
S9 1BW

T: +44 (0)1143 030 320

Useful Links

[Privacy Policy](#)

[Sitemap](#)

