

15CDV6 ALAŞIMLI ÇELİK

Yaygın Kullanım Alanları

Rulo Kafesler

Basıncılı kaplar

Roket Motoru Muhafazaları

Alt çerçeveler

Takip ve İtme çubukları

salıncaklar

Dikmeler

Dynamic Metals uzman bir alaşımlı çelik tedarikçisidir. Stok adetlerinde minimum sipariş sınırlaması olmayan çubuk, sac ve levha çeşitleri için bizimle iletişime geçin .

Teknik özellik

İlgili Özellikler

W.Nr 1.7734

AIR 9160C

GT1000

Özgül ağırlık

7.8 g/cm³

Kimyasal Bileşim (WT %)

	Min	Max
C	0.12	0.18
Si	-	0.20
Mn	0.80	1.10

S	-	0.015
P	-	0.020
Cr	1.25	1.50
Mo	0.80	1.00
V	0.20	0.30

Typical Mechanical Properties (in the solution treated condition)

	Condition	1.7734.2 (Annealed)	1.7734.4	1.7734.5	1.7745.6
0.2% Proof Stress	MPA	-	550	790	930
Tensile Strength	MPA	-	700	980-1180	1080-1250
Elongation	%	-	13	11	10
Reduction	HB	197	207	293-352	321-363

Need more information? **Get in touch**

General Enquiries

+44(0) 1525 217 556

Email us here

Head Office

40 Eden Way
Chartwell Business Park
Leighton Buzzard
Bedfordshire
LU7 4FY

T: +44 (0)1525 217 556

Conversion Centre

Suite 2 Meadowhall Riverside
Meadowhall Road
Sheffield
South Yorkshire
S9 1BW

T: +44 (0)1143 030 320

Useful Links

[Privacy Policy](#)

[Sitemap](#)

