

ACCIAIO INOSSIDABILE MARAGING 300

Maraging 300 (noto anche come Vascomax® 300) è un acciaio al 18% rinforzato con nichel e cobalto. È un materiale ad altissima resistenza che raggiunge un UTS di 1930 MPA dopo il trattamento termico. È prodotto tramite Vacuum Induction Melting (VIM) seguito da Vacuum Arc Remelting (VAR).

Specific Gravity													
8.0 g/cm3													
Typical Applications							Related Specifications						
Driveshafts							AMS 6514						
Gears							ASTM A538						
Fasteners							Mil-S-46850D						
Landing and Takeoff gear							UNS K93120						
Missile and ejector systems							W.Nr 1.6358						
Torsion springs													
Chemical Composition (Wt %)													
	C	Si	Mn	P	S	Al	Co	Ni	Mo	Ti	Cr	Cu	Fe
Min	–	–	–	–	–	0.05	8.5	18.00	4.6	0.5	–	–	Bal
Max	0.03	0.10	0.10	0.010	0.010	0.15	9.5	19.00	5.20	0.8	0.5	0.5	–
Typical Mechanical Properties after heat treatment													
0.2% Proof Stress								Tensile Strength		Elongation		Hardness	
MPA								MPA		%		HRC	
Min								Min		Min		Min	
1862								1930		5		52	
* Every effort has been made to ensure that our technical specifications are accurate. However, technical specifications included within Dynamic Metals Ltd should be used as a guideline only and are subject to change													

without notice.

General Enquiries

T: +44 (0) 1525 217 556 [\(tel:+4401525217556\)](tel:+4401525217556)

E: sales@dynamicmetalsltd.com [\(mailto:sales@dynamicmetalsltd.com\)](mailto:sales@dynamicmetalsltd.com)



UK Address:

Head Office

40 Eden Way
Chartwell Business Park
Leighton Buzzard
Bedfordshire
LU7 4FY

T: +44 (0)1525 217 556 [\(tel:+441525217556\)](tel:+441525217556)

Conversion Centre

Suite 2 Meadowhall Riverside
Meadowhall Road
Sheffield
South Yorkshire
S9 1BW

T: +44 (0)1143 030 320 [\(tel:+4401143030320\)](tel:+4401143030320)

Registered Office (only)

The Granary
Crowhill Farm Ravensden Road
Wilden
Bedfordshire
MK44 2QS

T: +44 (0)1525 217 556 [\(tel:+441525217556\)](tel:+441525217556)



[\(/media/zn2dbklo/cyber-essentials-certified-plus.png\)](#)



[\(/media/dyelbliq/cyber-essentials-certified.png\)](#)