

LEGA DI NICHEL C263 - AMS 5872, AMS 5886

C263 (AMS 5872, AMS 5886) è una lega di nichel-cobalto-cromo a fusione d'aria, indurimento per invecchiamento per dare un equilibrio accettabile di resistenza e duttilità a temperatura ambiente o ad temperatura elevata

Specific Gravity									
Typical Applications					Related Specifications				
					AMS 5872				
					BS HR 206				
					BS HR 10				
Chemical Composition (Wt %)									
	Ni	Co	Cr	Mo	Ti + Al	Fe	Cu	C	Si
Min	Bal	19	19	5.6	2.4	–	–	0.04	–
Max	Bal	21	21	6.1	2.8	0.7	0.2	0.08	0.4
Typical Mechanical Properties									
	0.2% Proof Stress	Tensile Strength	Elongation	Reduction of area	Hardness				
Content									
Hardness after Heat Treatment									

* Every effort has been made to ensure that our technical specifications are accurate. However, technical specifications included within Dynamic Metals Ltd should be used as a guideline only and are subject to change without notice.

General Enquiries

T: +44 (0) 1525 217 556 [\(tel:+4401525217556\)](tel:+4401525217556)

E: sales@dynamicmetalsltd.com [\(mailto:sales@dynamicmetalsltd.com\)](mailto:sales@dynamicmetalsltd.com)



UK Address:

Head Office

40 Eden Way
Chartwell Business Park
Leighton Buzzard
Bedfordshire
LU7 4FY

T: +44 (0)1525 217 556 [\(tel:+441525217556\)](tel:+441525217556)

Conversion Centre

Suite 2 Meadowhall Riverside
Meadowhall Road
Sheffield
South Yorkshire
S9 1BW

T: +44 (0)1143 030 320 [\(tel:+4401143030320\)](tel:+4401143030320)

Registered Office (only)

The Granary
Crowhill Farm Ravensden Road
Wilden
Bedfordshire
MK44 2QS

T: +44 (0)1525 217 556 [\(tel:+441525217556\)](tel:+441525217556)



[\(/media/zn2dbklo/cyber-essentials-certified-plus.png\)](#)



[\(/media/dyelbliq/cyber-essentials-certified.png\)](#)