

## ACCIAIO LEGATO EN24

Dynamic Metals è un fornitore di acciaio legato EN24 (W.Nr 1.6565, 817M40). Forniamo metalli di alta qualità e senza ordine minimo su barre, lamiere e piastre

| Specific Gravity                                                                                                                                                                                                                         |                         |                     |            |                      |          |                        |  |  |  |  |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|---------------------|------------|----------------------|----------|------------------------|--|--|--|--|
|                                                                                                                                                                                                                                          |                         |                     |            |                      |          |                        |  |  |  |  |
| Typical Applications                                                                                                                                                                                                                     |                         |                     |            |                      |          | Related Specifications |  |  |  |  |
|                                                                                                                                                                                                                                          |                         |                     |            |                      |          | 817M40                 |  |  |  |  |
| Chemical Composition (Wt %)                                                                                                                                                                                                              |                         |                     |            |                      |          |                        |  |  |  |  |
|                                                                                                                                                                                                                                          |                         |                     |            |                      |          |                        |  |  |  |  |
| Min                                                                                                                                                                                                                                      |                         |                     |            |                      |          |                        |  |  |  |  |
| Max                                                                                                                                                                                                                                      |                         |                     |            |                      |          |                        |  |  |  |  |
| Typical Mechanical Properties                                                                                                                                                                                                            |                         |                     |            |                      |          |                        |  |  |  |  |
|                                                                                                                                                                                                                                          | 0.2%<br>Proof<br>Stress | Tensile<br>Strength | Elongation | Reduction<br>of area | Hardness |                        |  |  |  |  |
|                                                                                                                                                                                                                                          |                         |                     |            |                      |          |                        |  |  |  |  |
| Content                                                                                                                                                                                                                                  |                         |                     |            |                      |          |                        |  |  |  |  |
|                                                                                                                                                                                                                                          |                         |                     |            |                      |          |                        |  |  |  |  |
|                                                                                                                                                                                                                                          |                         |                     |            |                      |          |                        |  |  |  |  |
| Hardness after Heat Treatment                                                                                                                                                                                                            |                         |                     |            |                      |          |                        |  |  |  |  |
|                                                                                                                                                                                                                                          |                         |                     |            |                      |          |                        |  |  |  |  |
| * Every effort has been made to ensure that our technical specifications are accurate. However, technical specifications included within Dynamic Metals Ltd should be used as a guideline only and are subject to change without notice. |                         |                     |            |                      |          |                        |  |  |  |  |

---

## General Enquiries

T: +44 (0) 1525 217 556 [\(tel:+4401525217556\)](tel:+4401525217556)

E: [sales@dynamicmetalsltd.com](mailto:sales@dynamicmetalsltd.com) [\(mailto:sales@dynamicmetalsltd.com\)](mailto:sales@dynamicmetalsltd.com)



### UK Address:

#### *Head Office*

40 Eden Way  
Chartwell Business Park  
Leighton Buzzard  
Bedfordshire  
LU7 4FY

T: +44 (0)1525 217 556 [\(tel:+441525217556\)](tel:+441525217556)

#### *Conversion Centre*

Suite 2 Meadowhall Riverside  
Meadowhall Road  
Sheffield  
South Yorkshire  
S9 1BW

T: +44 (0)1143 030 320 [\(tel:+4401143030320\)](tel:+4401143030320)

#### *Registered Office (only)*

The Granary  
Crowhill Farm Ravensden Road  
Wilden  
Bedfordshire  
MK44 2QS

T: +44 (0)1525 217 556 [\(tel:+441525217556\)](tel:+441525217556)



[\(/media/zn2dbklo/cyber-essentials-certified-plus.png\)](#)



[\(/media/dyelbliq/cyber-essentials-certified.png\)](#)