

## ALLOY 25 / L605 COBALT ALLOY

Cobalt Alloy 25/L605 has a carefully balanced composition of cobalt, chromium, tungsten, and other trace elements.

The main strengths of this alloy are its ability to resist corrosion and wear, as well as its capacity to endure high temperatures. Cobalt Alloy L605 maintains its structural integrity well, even when subjected to caustic environments, abrasive forces or scorching heat.

The main strength of Cobalt Alloy L605 is its hardness, which is achieved through a heat treatment process. This hardness is no mere boast - it translates into exceptional wear resistance that allows the alloy to shrug off the harshest conditions. Whether it's being subjected to relentless friction or operating in abrasive environments, L605 exhibits a tenacity that few materials can match. In industries where downtime is unacceptable and failure is not an option, L605 stands as a tireless workhorse, ready to take on the most punishing challenges.

But the capabilities of Cobalt Alloy L605 don't end there. Its remarkable strength at extreme heat levels means it is a good choice for high heat applications, e.g. Industrial Furnace Lines. From the blistering environments of aerospace applications to the furnace-like conditions of power generation and chemical processing plants, components crafted from this alloy stand unwavering, their structural integrity never compromised.

<b>Specific Gravity</b>										
9.14 g/cm <sup>3</sup>										
<b>Typical Applications</b>						<b>Related Specifications</b>				
Aircraft Engines						AMS 5759				
Gas Turbines						AMS 5537				
Ball Bearings										
Industrial Furnace Lines										
<b>Chemical Composition (Wt %)</b>										
	C	Mn	Si	P	S	Cr	Ni	W	FE	Co
<b>Min</b>	<b>0.05</b>	1	-	-	-	19	9	14	-	Bal
<b>Max</b>	<b>0.15</b>	2	0.4	0.04	0.03	21	11	16	3	
<b>Typical Mechanical Properties</b>										

	<b>0.2% Proof Stress</b>	<b>Tensile Strength</b>	<b>Elongation</b>	<b>Hardness</b>
	MPA	MPA	%	HB
<b>Content</b>	310	862	30	277

\* This data has been supplied in good faith and is indicative only. It has been provided for general information purposes only and is not to be relied upon in place of the full specification. Mechanical properties can vary considerably with different supply conditions such as heat treatment or temper and product dimensions.

No liability will be accepted by Dynamic Metals Ltd in respect of any action taken by any third party in reliance of any of the data provided.

The information provided in this datasheet has been taken from multiple recognised sources. No guarantee is given that the information is from the latest issue of these sources and no guarantee is given that the information in the datasheet is accurate or up to date.

Material supplied by Dynamic Metals Ltd may vary significantly from this data but will conform to the relevant and applicable standards. All transactions are subject to Dynamic Metals Ltd latest Terms and Conditions of Sale.

As the products detailed may be used for a wide variety of purposes and as Dynamic Metals Ltd has no control over their use; Dynamic Metals Ltd specifically excludes all conditions or warranties expressed or implied by statute or otherwise as to dimensions, properties and/or fitness for any particular purpose, whether expressed or implied.

Advice given by Dynamic Metals Ltd to any third party is given for that party's assistance only and without liability on the part of Dynamic Metals Ltd.

All transactions are subject to Dynamic Metals Ltd latest Terms and Conditions of Sale. The extent of the Company's liabilities to any customer is clearly set out in those Conditions; a copy of which is available by request or by downloading from our website.

## General Enquiries

T: +44 (0) 1525 217 556 [\(tel:+4401525217556\)](tel:+4401525217556)

E: [sales@dynamicmetalsltd.com](mailto:sales@dynamicmetalsltd.com) [\(mailto:sales@dynamicmetalsltd.com\)](mailto:sales@dynamicmetalsltd.com)



## UK Address:

### *Head Office*

40 Eden Way  
 Chartwell Business Park  
 Leighton Buzzard  
 Bedfordshire  
 LU7 4FY

T: +44 (0)1525 217 556 [\(tel:+441525217556\)](tel:+441525217556)

### *Conversion Centre*

Suite 2 Meadowhall Riverside  
 Meadowhall Road  
 Sheffield  
 South Yorkshire  
 S9 1BW

T: +44 (0)1143 030 320 [\\_\(tel:+4401143030320\)](tel:+4401143030320)

*Registered Office (only)*

The Granary  
Crowhill Farm Ravensden Road  
Wilden  
Bedfordshire  
MK44 2QS

T: +44 (0)1525 217 556 [\\_\(tel:+441525217556\)](tel:+441525217556)



[\(/media/zn2dbklo/cyber-essentials-certified-plus.png\)](#)



[\(/media/dyelbliq/cyber-essentials-certified.png\)](#)